

| FMSI Plate No. | FMSI Friction No. | Dynamic Part No. | Application | FMSI Plate No. | FMSI Friction No. | Dynamic Part No. | Application |
|----------------|-------------------|------------------|---|----------------|-------------------|------------------|---|
| D13 | 728A | DX52 | | D459 | 7339 | DX459 | With 'C' Clip; Inner Friction 1.89/.770/4.80, Outer Friction 1.77/.650/5.67 |
| D50 | 788 | DX50 | Thickness, .674/.514 | D505 | 7384 | DX505 | |
| D50A | 7013A | DX50 | Thickness, .674/.564 | D543 | 7081 | DX543 | |
| D52 | 728A | DX52 | Thickness, .624/.535 | D546 | 7425 | DX675 | MD/HD Trucks |
| D52A | 7214A | DX52 | Thickness, .580/.521 | D557 | 7436 | DX557 | |
| D53 | 787 | DX269 | | D604 | 7485 | DX686 | |
| D86 | 7019 | DX269 | | D605 | 7486 | DX434 | |
| D89 | 7024A | DX543 | Thickness, .795/.639 | D611 | 7298 | DX611 | |
| D89A | 7024B | DX543 | Thickness, .795/.639 | D614 | 7492 | DX614 | Thickness, .618/.480 |
| D92 | 7013A | DX50 | Thickness, .674/.564 | D614A | 7506 | DX614A | Thickness, .685/.575 |
| D120 | 7054 | DX450 | | D626 | 7503 | DX632 | |
| D122 | 728A | DX52 | | D632 | 7503 | DX632 | |
| D123 | 7019A | DX269 | | D646 | 7527 | DX701 | Medium Duty Trucks |
| D129 | 7024A | DX543 | | D651 | 7531 | DX651 | |
| D129A | 7024B | DX543 | | D655 | 7677 | DX655 | Thickness, .705 |
| D149 | 7081 | DX543 | | D655A | 7535 | DX655 | Thickness, .736 |
| D149A | 7081A | DX543 | | D675 | 7425 | DX675 | Medium Duty Trucks |
| D150 | 7082A | DX150 | | D679 | 7558 | DX679 | Heavy Duty Hauling and Towing |
| D153 | 7084A | DX153 | Thickness, .685/.530 | D686 | 7485 | DX686 | |
| D153A | 7280A | DX153 | Thickness, .650/.495 | D698 | 7387 | DX698 | With 2 Wear Sensors; with Center Rotation Lug |
| D184 | 7108 | DX717 | MD/HD Trucks; Thickness, 1.125 | D699 | 7574 | DX699 | |
| D184A | 7806 | DX717 | MD/HD Trucks | D701 | 7575 | DX701 | Medium Duty Trucks |
| D215 | 7136 | DX215 | | D702 | 7576 | DX702 | Thickness, .650; Heavy Duty Hauling and Towing |
| D224 | 7141 | DX224 | MD/HD Trucks | D702 | 7752 | DX702A | Thickness, .780; Heavy Duty Hauling and Towing |
| D224A | 7807 | DX224 | MD/HD Trucks | D711 | 7584 | DX711 | |
| D225 | 7142 | DX225 | MD/HD Trucks | D717 | 7815 | DX717 | Medium Duty Trucks |
| D225A | 7808 | DX225A | MD/HD Trucks; with NEC Kit | D734 | 7603 | DX734 | Dual Caliper; Medium Duty Truck; 8 Piece Set |
| D225B | 7813 | DX225 | MD/HD Trucks | D735 | 7604 | DX735 | 2 Pads Drilled; Dual Caliper; Medium Duty Truck; 8 Piece Set |
| D225C | 7818 | DX225 | MD/HD Trucks | D756 | 7625 | DX824 | D756 Not Drilled |
| D225D | 7819 | DX225 | MD/HD Trucks | D757 | 7626 | DX757 | |
| D228 | 7144 | DX228 | Thickness, .635 | D758 | 7627 | DX702 | |
| D228A | 7309 | DX228 | Thickness, .642 | D769 | 7636 | DX769 | Medium Duty Trucks |
| D228B | 7498 | DX228 | Thickness, .650 | D777 | 7644 | DX777 | |
| D236 | 7149 | DX236 | MD/HD Trucks; .1.000 | D784 | 7652 | DX784 | Length of Pad, 8.5"; Heavy Duty Towing and Hauling |
| D236A | 7809 | DX236 | MD/HD Trucks; .1.000 | D785 | 7653 | DX785 | Length of Pad, 7.0"; Heavy Duty Towing and Hauling |
| D269 | 7019 | DX269 | | D786 | 7654 | DX786 | With 66MM Brakes; Thickness, .799; Medium Duty Trucks |
| D269A | 7179 | DX269 | | D786A | 7655 | DX786A | With 73 MM Brakes; Thickness, .1.055; Medium Duty trucks |
| D269B | 7179 | DX269 | | D788 | 7658 | DX788 | |
| D303 | 7205 | DX434 | | D789 | 7659 | DX369 | |
| D306 | 7208 | DX228 | | D792 | 7700 | DX792 | Thickness, .640 |
| D313 | 7214 | DX52 | | D792A | 7662 | DX792A | Thickness, .673; Special NEC Kit for Heavy Duty Use |
| D346 | 7082 | DX150 | | D802 | 7673 | DX802 | |
| D360 | 788 | DX375 | | D812 | 7687 | DX812 | |
| D368 | 7259 | DX368 | | D814 | 7387 | DX698 | With 2 Wear Sensors; without Center rotation Lug |
| D369 | 7259 | DX369 | With 'C' Clip | D818 | 7693 | DX699 | |
| D369 | 7259 | DX369 | With 'C' Clip; For Heavy Duty Hauling and Towing | D821 | 7694 | DX859 | D821 Without Wear Sensors |
| D370 | 7260 | DX845 | With 'C' Clip; Inner Friction 1.89/.670/4.80, Outer Friction 1.79/.618/5.67 | D824 | 7625 | DX824 | Drilled; D756 Not Drilled |
| D375 | 7264 | DX375 | Thickness; .634/550 | D825 | 7697 | DX825 | Medium Duty Trucks |
| D375A | 7361 | DX375 | Thickness; .668/520 | | | | |
| D380 | 7815 | DX717 | MD/HD Trucks | | | | |
| D392 | 7280 | DX153 | | | | | |
| D411 | 7299 | DX411 | | | | | |
| D434 | 7321 | DX434 | Drilled | | | | |
| D438 | 7205 | DX434 | | | | | |
| D450 | 7330 | DX450 | | | | | |

FLEET VEHICLES/
LIGHT TRUCKS

MEDIUM/HEAVY
DUTY TRUCKS

NUMERICAL
LISTING

FMSI TO MONROE
INTERCHANGE

INSTALLATION TIPS

TECHNICAL
INFORMATION

FRICITION INTERCHANGE BY PLATE NUMBER



| FMSI Plate No. | FMSI Friction No. | Dynamic Part No. | Application | FMSI Plate No. | FMSI Friction No. | Dynamic Part No. | Application |
|----------------|-------------------|------------------|---|----------------|-------------------|------------------|---|
| D826 | 7698 | DX826 | Medium Duty Trucks | D1012 | 7916 | DX1012 | With Anti-Rattle Clip |
| D827 | 7699 | DX827 | Medium Duty Trucks | D1015 | 7918 | DX1015 | |
| D834 | 7707 | DX975 | | D1025 | 7929 | DX788 | |
| D842 | 7718 | DX702 | | D1027 | 7931 | DX1027 | |
| D845 | 7260 | DX845 | With 'C' Clip; Inner Friction 1.89/.670/4.80, Outer Friction 1.79/.618/5.67 | D1032 | 7636 | DX769 | Medium Duty Trucks |
| D845A | 7721 | DX845 | With 'C' Clip; Inner Friction 1.89/.670/4.80, Outer Friction 1.55/.614/5.65 | D1041 | 7945 | DX1041 | |
| D851 | 7727 | DX228 | | D1045 | 7948 | DX1045 | |
| D859 | 7694 | DX859 | With Wear Sensors | D1046 | 7949 | DX1046 | |
| D879 | 7584 | DX711 | | D1054 | 7959 | DX1054 | |
| D897 | 7774 | DX966A | | D1062 | 7968 | DX1062 | |
| D898 | 7775 | DX898 | | D1063 | 7918 | DX1015 | |
| D898 | 7867 | DX898 | | D1064 | 7969 | DX1064 | Medium Duty Trucks; DIH Parking Brake |
| D909 | 7788 | DX909 | | D1066 | 7972 | DX1066 | |
| D928A | 7970 | DX928A | 2 Pads with Wire Wear Sensors; Pad Length of 5.0" | D1067 | 7973 | DX1067 | |
| D949 | 7848 | DX949 | Bosch Caliper; Without Wire Wear Sensor; Pad Length of 6.5" | D1068 | 7973 | DX1068 | |
| D949A | 7848 | DX949A | Bosch Caliper; 2 Pads With Wire Wear Sensors; Pad Length of 6.5" | D1068A | 7973 | DX1068A | NEC Kit contains Anti Rattle Clip |
| D950 | 7849 | DX950 | Teves Caliper; Without Wire Wear Sensor; Pad Length of 6.2" | D1069 | 7974 | DX1069 | NEC Kit is for Single Rear Wheel Applications |
| D950A | 7849 | DX950A | Teves Caliper; 2 Pads With Wire Wear Sensors; Pad Length of 6.2" | D1069A | 7974 | DX1069A | NEC Kit is for Dual Rear Wheel Applications |
| D951 | 7850 | DX951 | Teves Caliper; Without Wire Wear Sensor; Pad Length of 5.6" | D1076 | 7981 | DX699 | |
| D951A | 7850 | DX951A | Teves Caliper; 2 Pads With Wire Wear Sensors; Pad Length of 5.6" | D1077 | 7982 | DX1077 | Thickness, .712 |
| D965 | 7864 | DX965 | | D1077A | 7865 | DX702A | Thickness, .780 |
| D966 | 7866 | DX966 | Thickness, .655 | D1079 | 7984 | DX1079 | |
| D966A | 7868 | DX966A | Thickness, .690 | D1083 | 7915 | DX1083 | With Drilled Radius for Anti-Rattle Clip, included in NEC Kit |
| D966B | 7774 | DX966A | Thickness, .697 | D1084 | 7991 | DX1084 | |
| D967 | 7869 | DX898 | Thickness, .610 | D1085 | 7992 | DX1085 | |
| D967A | 7867 | DX898 | Thickness, .610 | D1087 | 7945 | DX1041 | |
| D974 | 7881 | DX974 | Thickness, .670 | D1092 | 7997 | DX1092 | |
| D974A | 7875 | DX974A | Thickness, .790 | D1096 | 7865 | DX702A | |
| D974B | 7989 | DX974 | Thickness, .656 | D1136 | 8246 | DX949 | |
| D975 | 7707 | DX975 | | D1159 | 8269 | DX1159 | |
| D976 | 7877 | DX976 | For Heavy Duty Hauling and Towing | D1177 | 7849 | DX950 | |
| D989 | 7891 | DX989 | | D1183 | 8300 | DX1015 | |
| D1006 | 7909 | DX1006 | 16" Wheels; With Teves Caliper; Pad Length of 5.2" | D1194 | 8312 | DX1194 | |
| D1006A | 7909 | DX1006A | 2 Pads with Wire Wear Sensors; Teves Caliper; Pad Length of 5.2" | D1203 | 8323 | DX1203 | |
| D1010 | 7914 | DX1010 | Medium Duty Trucks | D1224 | 7693 | DX699 | |
| D1011 | 7915 | DX1083 | D1011 is w/o Drilled Radius; D1083 is w/Drilled Radius for Anti Rattle Clip | D1229 | 8348 | DX1006 | |
| | | | | D1229A | 8348 | DX1006A | |
| | | | | D1265 | 8382 | DX1265 | |
| | | | | D1268 | 8383 | DX1268 | |
| | | | | D1268W | 8383 | DX1268W | 2 Pads with Wire Wear Sensors |
| | | | | D1303 | 8419 | DX1303 | |
| | | | | D1304 | 8420 | DX1304 | |
| | | | | D1310 | 8425 | DX1310 | |
| | | | | D1311 | 8426 | DX1311 | |
| | | | | D1312 | 8427 | DX1312 | |
| | | | | D1323 | 8435 | DX1323 | |
| | | | | D1328 | 8440 | DX1328 | |
| | | | | D1329 | 8441 | DX1329 | |
| | | | | D1335 | 8446 | DX1335 | |



FRICITION INTERCHANGE BY SHOE NUMBER

| FMSI Shoe No. | BX Part No. | Application | FMSI Shoe No. | BX Part No. | Application |
|---------------|---------------|-------------|---------------|---------------|-------------|
| 9 | BX55 | - | 462 | BX462 | - |
| 10 | BX228 | - | 462 | BX462R | - |
| 31 | BX267 | - | 473 | BX473 | - |
| 33 | BX33 | - | 473 | BX473R | - |
| 55 | BX55 | - | 505 | BX505 | -w/ Pins |
| 56 | BX55 | - | 507 | BX521 | - |
| 78 | BX169R | - | 518 | BX521 | - |
| 155 | BX169R | - | 521 | BX521 | - |
| 161 | BX228 | - | 549 | BX549 | -w/ Pins |
| 169 | BX169R | - | 552 | BX552 | - |
| 181 | BX227 | - | 564 | BX564 | -w/ Pins |
| 227 | BX227 | - | 582 | BX582 | - |
| 228 | BX228 | - | 582 | BX582R | - |
| 242 | BX245 | - | 583 | BX583 | -w/ Pins |
| 245 | BX245 | - | 583 | BX583R | -w/ Pins |
| 246 | BX246 | - | 589 | BX589 | -w/ Pins |
| 263R | BX263 | - | 589 | BX589R | -w/ Pins |
| 263R | BX263R | - | 593 | BX675 | -w/ Pins |
| 267 | BX267 | - | S612 | BX612 | - |
| 280 | BX280 | - | S636 | BX636 | - |
| 280 | BX280R | - | S636 | BX636R | - |
| 290 | BX169R | - | S650 | BX245 | - |
| 314 | BX358 | -w/ Pins | S653 | BX473 | - |
| 316 | BX357 | -w/ Pins | S654 | BX675 | -w/ Pins |
| 357 | BX357 | -w/ Pins | S655 | BX451R | - |
| 357 | BX357R | -w/ Pins | S656 | BX452R | - |
| 358 | BX358 | -w/ Pins | S675 | BX675 | -w/ Pins |
| 358 | BX358R | -w/ Pins | S675 | BX675R | -w/ Pins |
| 363 | BX363 | -w/ Pins | S699 | BX699 | - |
| 366 | BX366 | - | S723 | BX723 | -w/ Pins |
| 419 | BX419R | - | S723 | BX723R | -w/ Pins |
| 445 | BX445 | -w/ Pins | S726 | BX726 | - |
| 445 | BX445R | -w/ Pins | S734 | BX723 | -w/ Pins |
| 446 | BX446 | -w/ Pins | S752 | BX752 | - |
| 446 | BX446R | -w/ Pins | S764 | BX764 | -w/ Pins |
| 449 | BX449 | - | S771 | BX771 | - |
| 449 | BX449R | - | S772 | BX772 | - |
| 450 | BX450R | - | S776 | BX723 | -w/ Pins |
| 451 | BX451R | - | S781 | BX781 | - |
| 452 | BX452R | - | S855 | BX855 | -w/ Levers |

FLEET VEHICLES/
LIGHT TRUCKS

MEDIUM/HEAVY
DUTY TRUCKS

NUMERICAL
LISTING

FMSI TO MONROE
INTERCHANGE

INSTALLATION TIPS

TECHNICAL
INFORMATION